

WT TRI COLOR- OR16

Physical	
Resolution	40(H)×32(W)
Pixel Pitch	16 mm
LED Configuration	2R1G 3mm Oval
Pixel Density	3906 pixels/m ²
Size	640×512×167mm
Strip Quantity	10
Weight	40Kg
Mechanical Ratings	
Surface Flatness	Gap≤0.5mm
Optical Ratings	
Brightness	≥5,000 cd/m ²
View Angle (Horizontal)	110°
View Distance	≥10m
Gray Scale	8bits input, correction with 14bits
Display Color	16.7 Million
Brightness Adjustment	0~100% 10 level
Power Supply	
Operation Power	90~260V 50~60Hz
Max. Power Consumption	500 W/m ²
Average Power Consumption	170 W/m ²
Control System	
Control Mode	Synchronous display with control PC by DVI
Frame Update Frequency	60~85Hz
Screen Refresh Frequency	300~1000Hz
Gamma Correction	-5.0~+5.0
Support Input	Composite, S-Video, Component, VGA, DVI, HDMI, HD_SDI
Control Distance	Ethernet cable≤80m or Fiber Optic>80m
Supporting VGA Mode	1024×768, 1280×1024, 1600×1200, 1920×1280
Brightness Correction	Pixel, Module, Cabinet
Environmental	
Operating Temperature	-20°C ~+60°C
Operating Humidity	10~95% RH

Operating Life	100,000 hours
MTBF	5000 hours
Protection Level	IP65(front)/IP54(rear)
LED Specification	
Package	3mm Oval Lamp
Intensity	Red 122~170 mcd Green 233~333 mcd
Wavelength	Red 625~630 nm Green 520~525 nm

